

View Online at <https://aerobasegroup.com/nsn/5305-01-279-2333>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

2.000 inches

Fastener Length:

Between 2.190 inches and 2.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 1.107 inches and 1.125 inches

Head Height:

Between 0.740 inches and 0.750 inches

Locking Feature:

Patch threads or pellet threads or strip threads

Internal Drive Style:

Hexagon

Thread Diameter:

0.750 inches

Width Across Flats:

Between 0.625 inches and 0.631 inches

Thread Qty Per Inch (tpi):

16

Min. Tensile Strength (psi):

170000 pounds per square inch

Hardness Rating:

37.0 rockwell c fastener and 45.0 rockwell c fastener

Minimum Yield Strength:

150000 pounds per square inch

Material:

Steel fastener

Surface Treatment:

Cadmium fastener and chromate fastener

Surface Treatment Specification:

Qq-p-416, type 2 class 2 federal specification single treatment response fastener

Thread Series Designator:

Unrf

Specification Data:

80205-nas1351 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0