

View Online at <https://aerobasegroup.com/nsn/5305-01-279-2339>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 1.000 inches and 1.188 inches

Fastener Length:

Between 2.406 inches and 2.500 inches

Head Height:

Between 0.226 inches and 0.243 inches

Width Between Flats:

Between 0.561 inches and 0.562 inches

Shank Unthreaded Hole Diameter:

0.105 inches first hole and 0.113 inches first hole

Thread Diameter:

0.375 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

150000 pounds per square inch

Hardness Rating:

33.0 rockwell c and 39.0 rockwell c

Minimum Yield Strength:

130000 pounds per square inch

Distance From Head Largest Bearing Surface To Shank Hole Center:

2.240 inches first hole and 2.354 inches first hole

Surface Finish:

63.0 microinches threads

Material:

Steel

Material Specification:

Sae j429 grade 8 assn standard single material response or astm a354 grade bd assn standard single material response

Surface Treatment:

Phosphate zinc

Surface Treatment Specification:

Dod-p-16232 military specification single treatment response

Thread Series Designator:

Unf

Specification Or Standard:

2 type and 10p style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

spec.