

View Online at <https://aerobasegroup.com/nsn/5305-01-279-2342>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.631 inches and 0.651 inches

Fastener Length:

Between 0.937 inches and 0.984 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.752 inches and 0.762 inches

Grip Diameter:

Between 0.3733 inches and 0.3742 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.375 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Width Across Flats:

Between 0.220 inches and 0.222 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 or steel comp 8740 or steel comp 4340

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-6049 military specification 2nd material response or mil-s-8844 military specification 3rd material response or ams6414 assn standard 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas336 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.