# NSN 5305-01-280-3275

Machine Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-280-3275



# Thread Class: 3a Thread Direction: Right-hand Thread Length:

Between 0.140 inches and 0.155 inches

#### Fastener Length:

Between 0.172 inches and 0.219 inches

#### Head Style:

Hexagon

Head Height:

Between 0.105 inches and 0.120 inches

#### Width Between Flats:

Between 0.305 inches and 0.314 inches

#### Internal Drive Style:

#### Cross recess type ii

**Thread Diameter:** 

0.190 inches

#### **Features Provided:**

Finished head

# Thready Qty Per Inch (tpi):

32

#### Min. Tensile Strength (psi):

160000 pounds per square inch

Screw Material:

Iron alloy 660

#### **Screw Material Specification:**

Ams5731 assn standard single material response or ams5737 k66286 assn standard single material response

#### Screw Surface Treatment:

Passivate

# Screw Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# Supplementary Features:

Int drive recess ms9006-2

# **Thread Series Designator:**

Unjf

### Specification Data:

80205-nas1802 professional/industrial association standard

# Shelf Life:

N/a

# Unit Of Measure:

--

# NSN 5305-01-280-3275

Machine Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A500d0

