NSN 5305-01-280-3645



Machine Screw - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5305-01-280-3645 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.719 inches and 0.750 inches **Fastener Length:** 0.750 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 80000 pounds per square inch **Screw Material:** Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel comp 385 **Screw Surface Treatment: Passivate Screw Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Special Features:** Paint top of head per 133c133, cagec 97942 Color: Black **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

Fiig: A500d0

No

Demilitarization: