Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-280-5664

| Thread Class:   |
|---|
| 3a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.160 inches  |
| Fastener Length:  |
| 0.500 inches  |
| Head Style:   |
| Flat chamfer  |
| Head Diameter:  |
| Between 0.262 inches and 0.270 inches                                   |
| Head Height:  |
| Between 0.159 inches and 0.164 inches                                   |
| First Diameter From Head:   |
| 0.114 inches  |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| 0.340 inches  |
| Internal Drive Style:   |
| Hexagon   |
| Thread Diameter:  |
| 0.164 inches  |
| Width Across Flats:   |
| Between 0.1406 inches and 0.1426 inches                                 |
| Thready Qty Per Inch (tpi):   |
| 32  |
| Externally Relieved Body Diameter Quantity:                             |
| 1   |
| Material:   |
| Steel   |
| Surface Treatment:  |
| Cadmium and chromate  |
| Surface Treatment Specification:  |
| Qq-p-416 type 2 cl 3 federal specification single treatment response    |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| -   |
| Demilitarization:   |
| No  |
|   |

## NSN 5305-01-280-5664

Externally Relieved Body Screw - Page 2 of 2

Fiig: A003b0

