## NSN 5305-01-280-5705



Socket Head Cap Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-280-5705 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.077 inches and 0.170 inches **Fastener Length:** Between 0.219 inches and 0.250 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.322 inches and 0.385 inches **Locking Feature:** Strip threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 36.0 rockwell c fastener and 40.0 rockwell c fastener **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 32.0 microinches threads Material: Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or steel comp 8735 fastener or steel comp 6150 fastener **Surface Treatment:** Cadmium fastener and chromate fastener **Surface Treatment Specification:** 

Qq-p-416, type 2 class 2 federal specification single treatment response fastener

**Thread Series Designator:** 

Unjf

**Specification Data:** 

80205-nas1189 professional/industrial association standard

Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5305-01-280-5705

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0