NSN 5305-01-280-6701

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-280-6701 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.845 inches and 0.938 inches **Fastener Length:** Between 0.907 inches and 0.938 inches **Head Style:** Fillister **Head Diameter:** Between 0.221 inches and 0.226 inches **Head Height:** Between 0.074 inches and 0.086 inches **Internal Drive Style:** Torque set **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** Between 36.0 rockwell c and 40.0 rockwell c **Product Name:** Navy special project **Screw Material:** Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 8735 or steel comp 6150 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1101 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5305-01-280-6701

Machine Screw - Page 2 of 2



Fiig:

A500d0