Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-280-6711



steel comp 8735 fastener or steel comp 6150

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.335 inches and 0.402 inches
Fastener Length:
Between 0.407 inches and 0.438 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.126 inches and 0.176 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.086 inches
Thready Qty Per Inch (tpi):
56
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
36.0 rockwell c fastener and 40.0 rockwell c fastener
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Surface Finish:
32.0 microinches threads
Product Name:
Navy special project
Material:
Steel comp e4340 fastener or steel comp 4140 fastener or steel comp 8740 fastener or
fastener
Surface Treatment:
Cadmium fastener and chromate fastener
Surface Treatment Specification:
Qq-p-416 ty2 cl2 federal specification single treatment response fastener
Thread Series Designator:
Unjc
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-280-6711

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

