

View Online at <https://aerobasegroup.com/nsn/5305-01-280-6737>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.380 inches and 0.432 inches

Fastener Length:

Between 1.890 inches and 1.922 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.338 inches and 0.381 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.190 inches

Grip Length:

Between 1.490 inches and 1.510 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp xm-13

Material Specification:

Ams 5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 type 2, cl 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.