

View Online at <https://aerobasegroup.com/nsn/5305-01-280-6740>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.338 inches and 0.388 inches

Fastener Length:

Between 1.160 inches and 1.190 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.339 inches and 0.381 inches

Head Height:

Between 0.439 inches and 0.459 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.190 inches

Grip Length:

Between 0.802 inches and 0.822 inches

Features Provided:

Sealing ring and cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Product Name:

Navy special project

Special Features:

O-ring floursilicone rubber per mil-r-6855 cl 1 gr 60

Material:

Iron alloy 660 fastener

Material Specification:

Ams 5731 assn standard single material response fastener

Surface Treatment:

Passivate fastener

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response fastener

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0