

View Online at <https://aerobasegroup.com/nsn/5305-01-280-6744>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.476 inches and 0.526 inches

Fastener Length:

Between 1.048 inches and 1.078 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.429 inches and 0.479 inches

Grip Diameter:

Between 0.311 inches and 0.312 inches

Internal Drive Style:

Torque-set ribbed

Thread Diameter:

0.312 inches

Grip Length:

Between 0.552 inches and 0.572 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Hardness Rating:

36.0 rockwell c and 40.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp 4140 or steel comp e4340 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416, type 2, cl 2 federal specification single treatment response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1581 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.