NSN 5305-01-281-0895

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-281-0895 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.359 inches and 0.391 inches **Fastener Length:** Between 0.922 inches and 0.954 inches **Head Style:** Double chamfer **Head Diameter:** Between 0.433 inches and 0.443 inches **Head Height:** Between 0.234 inches and 0.266 inches **First Diameter From Head:** Between 0.115 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.531 inches and 0.595 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Copper alloy 360 **Material Specification:** Qq-b-626 comp 22 federal specification single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:**

No

NSN 5305-01-281-0895

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0