Hexagon Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-281-7038

Thread Class: 3a Thread Direction: Right-hand Thread Length: 1.000 inches Fastener Length: Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Head Height: Between 0.226 inches and 0.562 inches Thread Diameter: 0.375 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc Shelf Life:
Thread Direction: Right-hand Thread Length: 1.000 inches Fastener Length: Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Right-hand Thread Length: 1.000 inches Fastener Length: Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thread Y Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Thread Length: 1.000 inches Fastener Length: Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
1.000 inches Fastener Length: Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Fastener Length:Between 3.190 inches and 3.250 inchesHead Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.562 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):16Material:SteelMaterial Specification:Sae gr 5 assn standard single material responseSurface Treatment:Zinc and chromateSurface Treatment Specification:Ms20 cagec 10988 mfr ref single treatment responseThread Series Designator:Unc
Between 3.190 inches and 3.250 inches Head Height: Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Head Height:Between 0.226 inches and 0.243 inchesWidth Between Flats:Between 0.551 inches and 0.562 inchesThread Diameter:0.375 inchesThready Qty Per Inch (tpi):16Material:SteelMaterial Specification:Sae gr 5 assn standard single material responseSurface Treatment:Zinc and chromateSurface Treatment Specification:Ms20 cagec 10988 mfr ref single treatment responseThread Series Designator:Unc
Between 0.226 inches and 0.243 inches Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Width Between Flats: Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Between 0.551 inches and 0.562 inches Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Thread Diameter: 0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
0.375 inches Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Thready Qty Per Inch (tpi): 16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
16 Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Material: Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Steel Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Material Specification: Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Sae gr 5 assn standard single material response Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Surface Treatment: Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Zinc and chromate Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Surface Treatment Specification: Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Ms20 cagec 10988 mfr ref single treatment response Thread Series Designator: Unc
Thread Series Designator: Unc
Unc
Shalf Life:
Sheh Lhe.
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A003b0