## NSN 5305-01-281-7149

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-281-7149 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.375 inches and 0.380 inches **Fastener Length:** 0.937 inches **Head Style:** Knurled no. 1 **Head Diameter:** Between 0.437 inches and 0.442 inches **Head Height:** Between 0.250 inches and 0.266 inches **First Diameter From Head:** Between 0.120 inches and 0.125 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.562 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a582 assn standard single material response or mil-w-52263 military specification single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-281-7149

Externally Relieved Body Screw - Page 2 of 2



em			

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263 spec.