

View Online at <https://aerobasegroup.com/nsn/5305-01-281-9195>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 1.330 inches and 1.500 inches

**Fastener Length:**

Between 1.440 inches and 1.500 inches

**Head Style:**

Square

**Head Height:**

Between 0.224 inches and 0.245 inches

**Width Between Flats:**

Between 0.302 inches and 0.312 inches

**Point Style:**

Cup

**Internal Drive Style:**

W/o internal drive

**Thread Diameter:**

0.312 inches

**Thready Qty Per Inch (tpi):**

18

**Hardness Rating:**

30.0 rockwell c and 37.0 rockwell c

**Material:**

Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1035 or steel comp 1037 or steel comp 1038 or steel comp 1039 or steel comp 1040 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel comp 1212 or steel comp 1213 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144

**Material Specification:**

66 federal standard all material responses

**Surface Treatment:**

Zinc

**Surface Treatment Specification:**

Astm b633 assn standard single treatment response

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 4 style

**Departure From Cited Designator:**

As modified by surface treatment

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

No

**Fig:**

A003b0