## NSN 5305-01-281-9202

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-281-9202

The strains at this point action and a second strain action at the second strain action action at the second strain action at the second strain action at the second strain action action at the second strain action at the second strain action action at the second strain action at the second strain action action at the second strain action at the second strain action actio
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 1.377 inches and 1.500 inches
Fastener Length:
Between 1.460 inches and 1.500 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.303 inches and 0.312 inches
Head Height:
Between 0.185 inches and 0.190 inches
Hole Diameter:
Between 0.044 inches and 0.050 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.156 inches
Hole Quantity:
6
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
180000 pounds per square inch
Hardness Rating:
38.0 rockwell c and 45.0 rockwell c
Hole Configuration Style:
Round internal hexagon
Surface Finish:
63.0 microinches bearing surface of head
Material:
Steel
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 type 2 cl 3 assn standard single treatment response

## NSN 5305-01-281-9202

Socket Head Cap Screw - Page 2 of 2



Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0