NSN 5305-01-282-3378

Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-282-3378
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 2.620 inches and 3.000 inches
Fastener Length:
Between 2.820 inches and 3.000 inches
Head Style:
Square
Head Height:
Between 0.544 inches and 0.582 inches
Width Between Flats:
Between 0.729 inches and 0.750 inches
Point Style:
Cup
Internal Drive Style:
W/o internal drive
Thread Diameter:
0.750 inches
Thready Qty Per Inch (tpi):
10
Hardness Rating:
30.0 rockwell c and 37.0 rockwell c
Product Name:
Setscrew
Material:
Steel comp 1010 or steel comp 1011 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018
or steel comp 1019 or steel comp 1020 or steel comp 1035 or steel comp 1536 or steel comp 1037 or steel comp 1038 or steel comp
1039 or steel comp 1040 or steel comp 1541 or steel comp 1042 or steel comp 1043 or steel comp 1044 or steel comp 1045 or steel
comp 1212 or steel comp 1213 or steel comp 1137 or steel comp 1139 or steel comp 1140 or steel comp 1141 or steel comp 1144 or
steel comp 12l14
Material Specification:
66 federal standard all material responses
Surface Treatment:
Zinc
Surface Treatment Specification:
Astm b633 assn standard single treatment response
Thread Series Designator:
Unc
Specification Or Standard:
1 type and 4 style

Shalf Lifa:

Departure From Cited Designator:As modified by surface treatment

NSN 5305-01-282-3378

Setscrew - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A003b0