NSN 5305-01-282-5678

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-282-5678 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.314 inches and 0.364 inches Fastener Length: Between 0.762 inches and 0.792 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.294 inches and 0.332 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.164 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: Between 36.0 rockwell c and 40.0 rockwell c **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Product Name:** Navy special project **Screw Material:** Steel comp 4140 or steel comp 4340 or steel comp 8740 **Screw Surface Treatment:** Cadmium and chromate **Screw Surface Treatment Specification:** Qq-p-416, type 2, cl 2 federal specification single treatment response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1221 professional/industrial association standard

•		
Shelf Life:		
N/a		
Unit Of Measure:		
Demilitarization:		
No		

NSN 5305-01-282-5678

Machine Screw - Page 2 of 2



Fiig:

A500d0