## NSN 5305-01-282-5682

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-282-5682 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.067 inches and 0.125 inches **Fastener Length:** Between 0.095 inches and 0.125 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.112 inches and 0.118 inches **Head Height:** Between 0.070 inches and 0.073 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.073 inches Width Across Flats: Between 0.063 inches and 0.064 inches Thready Qty Per Inch (tpi): 72 Min. Tensile Strength (psi): 180000 pounds per square inch Hardness Rating: 39.0 rockwell c and 45.0 rockwell c Minimum Yield Strength: 155000 pounds per square inch Material: Steel **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 ty2 cl2 federal specification single treatment response **Thread Series Designator:** Unrf **Specification Data:** 80205-nas1351 professional/industrial association standard Shelf Life: N/a

\_\_

**Unit Of Measure:** 

## NSN 5305-01-282-5682

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0