## NSN 5305-01-282-6142

3a

32

N/a

Socket Head Cap Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-282-6142



## **Thread Class: Thread Direction: Right-hand Thread Length:** Between 0.095 inches and 0.188 inches Fastener Length: Between 0.157 inches and 0.188 inches **Head Style:** Pan **Head Diameter:** Between 0.256 inches and 0.270 inches **Head Height:** Between 0.087 inches and 0.097 inches Locking Feature: Patch threads **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Hardness Rating: 36.0 rockwell c and 40.0 rockwell c Surface Finish: 32.0 microinches bearing surface of head Material: Plastic polyamide locking feature Material Specification: Ams 5737 assn standard single material response fastener Surface Treatment: Passivate fastener Surface Treatment Specification: Qq-p-35 federal specification single treatment response fastener **Thread Series Designator:** Unjc **Specification Data:** 80205-nas1190 professional/industrial association standard Shelf Life:

## NSN 5305-01-282-6142

Socket Head Cap Screw - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

