NSN 5305-01-282-7496

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-282-7496

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.625 inches
Fastener Length:
Between 0.720 inches and 0.750 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.154 inches and 0.161 inches
Head Height:
Between 0.095 inches and 0.099 inches
Locking Feature:
Patch threads or pellet threads or strip threads
Internal Drive Style:
Hexagon
Thread Diameter:
0.099 inches
Width Across Flats:
Between 0.078 inches and 0.079 inches
Thready Qty Per Inch (tpi):
48
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Material:
Steel comp 302 fastener or steel comp 304 fastener or steel comp 305 fastener or steel comp 316 fastener or steel comp 384 fastener
Surface Treatment:
Passivate fastener
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response fastener
Thread Series Designator:
Unrc
Specification Data:
80205-nas1352 professional/industrial association standard
Shelf Life:

N/a

NSN 5305-01-282-7496

Socket Head Cap Screw - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0