## NSN 5305-01-282-7503

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-282-7503 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.476 inches and 0.526 inches **Fastener Length:** Between 0.736 inches and 0.766 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.597 inches and 0.612 inches **Head Height:** Between 0.176 inches and 0.188 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.240 inches and 0.260 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 160000 pounds per square inch Surface Finish: 32.0 microinches threads Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** 

Unjf

Specification Data:

80205-nas1578 professional/industrial association standard

Shelf Life:

N/a

## NSN 5305-01-282-7503

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i> )+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0