NSN 5305-01-282-7503

Close Tolerance Screw - Page 1 of 2





View Online at https://aerobasegroup.com/nsn/5305-01-282-7503

Th	read Class:
3a	
Th	ead Direction:
Rig	ht-hand
Th	read Length:
Bet	ween 0.476 inches and 0.526 inches
Fas	stener Length:
Bet	ween 0.736 inches and 0.766 inches
Hea	ad Style:
Pa	n no. 2
Hea	ad Diameter:
Bet	ween 0.597 inches and 0.612 inches
Hea	ad Height:
Bet	ween 0.176 inches and 0.188 inches
Gri	p Diameter:
Bet	ween 0.3110 inches and 0.3120 inches
Inte	ernal Drive Style:
Tor	que-set ribbed
Th	read Diameter:
0.3	12 inches
Gri	p Length:
Bet	ween 0.240 inches and 0.260 inches
Th	eady Qty Per Inch (tpi):
24	
Mir	n. Tensile Strength (psi):
160	0000 pounds per square inch
Su	face Finish:
32.	0 microinches threads
Ма	terial:
Iror	n alloy 660
Ма	terial Specification:
Am	s5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
ma	terial response
Su	face Treatment:
Pas	ssivate
Su	face Treatment Specification:
Qq	-p-35 federal specification single treatment response
Th	read Series Designator:
Unj	f
Sp	ecification Data:
802	205-nas1578 professional/industrial association standard
Sh	elf Life:

N/a

NSN 5305-01-282-7503

Close Tolerance Screw - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0