# NSN 5305-01-282-9200

Panel Screw Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-282-9200



#### Thread Class:

2a

**Thread Direction:** 

**Right-hand** 

# Thread Length:

Between 0.585 inches and 0.615 inches

#### Fastener Length:

Between 1.653 inches and 1.701 inches

#### Head Style:

Hexagon

Head Height:

Between 0.172 inches and 0.190 inches

# Width Between Flats:

Between 0.367 inches and 0.375 inches

# Thread Diameter:

0.250 inches

# Thready Qty Per Inch (tpi):

28

# Min. Tensile Strength (psi):

175000 pounds per square inch

# Hardness Rating:

35.0 rockwell c primary washer and 43.0 rockwell c primary washer

# **Special Features:**

Knurl on sleeve 20 wide min; 0.375-24unf-2b

# Material:

Steel comp xm-13 fastener

# **Material Specification:**

Qq-w-423 cond b federal specification single material response spring

# Surface Treatment:

Passivate

# Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unf

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A003b0

NSN 5305-01-282-9200

Panel Screw Assembly - Page 2 of 2

# Mil-std (military Standard):

Mil-s-5059 spec.

