

View Online at <https://aerobasegroup.com/nsn/5305-01-283-0787>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.469 inches and 0.500 inches

Fastener Length:

Between 1.094 inches and 1.125 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.447 inches and 0.507 inches

Internal Drive Style:

Cross recess type 1

Thread Diameter:

0.250 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Hardness Rating:

Between 26.0 rockwell c and 32.0 rockwell c

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 8740 or steel comp 8630

Screw Material Specification:

Mil-s-6049, uns g8740 military specification 1st material response or mils-6040, uns g8630 military specification 2nd material response

Supplementary Features:

No surf. Fin. Plating; aircraft struct appl

Thread Series Designator:

Unf

Specification Data:

96906-ms24694 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A500d0

Mil-std (military Standard):

Mil-s-6049 spec.