

View Online at <https://aerobasegroup.com/nsn/5305-01-283-0787>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.469 inches and 0.500 inches

**Fastener Length:**

Between 1.094 inches and 1.125 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.447 inches and 0.507 inches

**Internal Drive Style:**

Cross recess type 1

**Thread Diameter:**

0.250 inches

**Features Provided:**

Finished head

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

125000 pounds per square inch

**Hardness Rating:**

Between 26.0 rockwell c and 32.0 rockwell c

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Screw Material:**

Steel comp 8740 or steel comp 8630

**Screw Material Specification:**

Mil-s-6049, uns g8740 military specification 1st material response or mils-6040, uns g8630 military specification 2nd material response

**Supplementary Features:**

No surf. Fin. Plating; aircraft struct appl

**Thread Series Designator:**

Unf

**Specification Data:**

96906-ms24694 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0

**Mil-std (military Standard):**

Mil-s-6049 spec.