NSN 5305-01-283-2422 Setscrew - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-283-2422
Thread Class:
3a
Thread Direction:
Right-hand
Fastener Length:
Between 0.928 inches and 0.948 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.125 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Point Length:
0.100 inches
Point Diameter:
Between 0.142 inches and 0.147 inches
Point Style:
Chamfer dog
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.125 inches
Thready Qty Per Inch (tpi):
32
Point Chamfer Angle:
45.0 degrees
Special Features:
Slot through shank, 0.044 in. Min. 0.054 in. Max. Width
Material:
Steel comp 302 or steel comp 304 or steel comp 304l or steel comp 305 or steel comp 309 or steel comp 310 or steel comp 316 or steel
comp 316l or steel comp 317 or steel comp 321 or steel comp 347
Surface Treatment:
Cadmium and chromate
Surface Treatment Specification:
Qq-p-416 type 2 cl 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-283-2422

Setscrew - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0