## NSN 5305-01-283-2520

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-283-2520

| view Online at https://aerobasegroup.com/nsn/0000-01-200-2020  |
|--|
| Thread Class:  |
| За   |
| Thread Direction:  |
| Right-hand   |
| Thread Length:   |
| Between 0.173 inches and 0.253 inches  |
| Fastener Length:   |
| 0.410 inches   |
| Head Style:  |
| Flat countersunk   |
| Head Diameter:   |
| 0.335 inches   |
| nternal Drive Style:   |
| Cross recess type 1  |
| Material Accommodated Thickness:   |
| Between 0.090 inches and 0.125 inches  |
| Thread Diameter:   |
| 0.164 inches   |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Min. Tensile Strength (psi):   |
| 140000 pounds per square inch  |
| Hardness Rating:   |
| 40.0 rockwell c and 42.0 rockwell c  |
| Countersink Angle:   |
| 100.0 degrees  |
| Material:  |
| ron alloy 660 fastener   |
| Material Specification:  |
| Qq-a-225/8 federal specification single material response stand-off  |
| Surface Treatment:   |
| Passivate fastener   |
| Surface Treatment Specification:   |
| Qq-p-35 type 1 federal specification single treatment response fastener or qq-p-35 type 2 federal specification single treatment response  |
| astener or qq-p-35 type 3 federal specification single treatment response fastener   |
| Thread Series Designator:  |
| Jnc State of the s |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5305-01-283-2520

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-a-8625 spec.