

View Online at <https://aerobasegroup.com/nsn/5305-01-283-4204>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.625 inches

Fastener Length:

Between 1.210 inches and 1.250 inches

Head Style:

Flat chamfer

Head Diameter:

Between 0.134 inches and 0.140 inches

Head Height:

Between 0.083 inches and 0.086 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.086 inches

Width Across Flats:

Between 0.078 inches and 0.079 inches

Thready Qty Per Inch (tpi):

56

Min. Tensile Strength (psi):

80000 pounds per square inch

Hardness Rating:

80.0 rockwell b

Minimum Yield Strength:

30000 pounds per square inch

Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

Material Specification:

Astm a493 assn standard all material responses

Surface Treatment:

Passivate

Surface Treatment Specification:

Astm a380 assn standard single treatment response

Thread Series Designator:

Unrc

Specification Data:

80205-nas1352 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0