

View Online at <https://aerobasegroup.com/nsn/5305-01-283-4598>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.375 inches

Fastener Length:

Between 1.235 inches and 1.265 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.625 inches and 0.635 inches

Grip Diameter:

0.311 inches

Shank Unthreaded Hole Diameter:

0.076 inches first hole and 0.086 inches first hole

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.312 inches

Grip Length:

Between 0.865 inches and 0.885 inches

Features Provided:

Finished head

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Distance From Head Largest Bearing Surface To Shank Hole Center:

1.131 inches first hole and 1.141 inches first hole

Material:

Titanium alloy uns r56400

Material Specification:

Ams4967 assn standard single material response

Thread Series Designator:

Unjf

Specification Data:

80205-nas1155 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0