NSN 5305-01-283-4618

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-283-4618 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.360 inches and 0.390 inches **Fastener Length:** Between 1.735 inches and 1.765 inches **Head Style:** Knurled no. 4 **Head Diameter:** Between 0.750 inches and 0.765 inches **Head Height:** Between 0.240 inches and 0.260 inches **First Diameter From Head:** Between 0.170 inches and 0.180 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 1.365 inches and 1.385 inches **Point Style:** Cone **Internal Drive Style:** Slot **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): 20 **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Astm a581 assn standard single material response or astm a582 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-283-4618

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0