

View Online at <https://aerobasegroup.com/nsn/5305-01-283-6662>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.408 inches and 0.500 inches

**Fastener Length:**

Between 0.470 inches and 0.500 inches

**Head Style:**

Flat chamfer

**Head Diameter:**

Between 0.218 inches and 0.226 inches

**Head Height:**

Between 0.134 inches and 0.138 inches

**Locking Feature:**

Patch threads or pellet threads or strip threads

**Internal Drive Style:**

Hexagon

**Thread Diameter:**

0.138 inches

**Width Across Flats:**

Between 0.109 inches and 0.111 inches

**Thready Qty Per Inch (tpi):**

32

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Hardness Rating:**

33.0 rockwell c fastener and 42.0 rockwell c fastener

**Minimum Yield Strength:**

120000 pounds per square inch

**Material:**

Plastic polyamide locking feature

**Material Specification:**

Ams5731 assn standard single material response fastener or ams5737 assn standard single material response fastener

**Surface Treatment:**

Passivate fastener

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response fastener

**Thread Series Designator:**

Unrc

**Specification Data:**

80205-nas1352 professional/industrial association standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0