## NSN 5305-01-283-9898

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-283-9898

The state of the s
Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.155 inches and 0.175 inches
Fastener Length:
Between 0.290 inches and 0.310 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.470 inches and 0.490 inches
Head Height:
0.075 inches
Shoulder Diameter:
0.197 inches first shoulder and 0.211 inches first shoulder
Shoulder Length:
0.080 inches first shoulder
Internal Drive Style:
Slot
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Shoulder Shape:
Round first shoulder
Special Features:
Thread relief undercut 0.140 in. Dia; 0.055 in. Lg; surface finish on shoulder and bearing surface 32.0 microinches
Material:
Steel comp 303se
Material Specification:
Astm a582 cond a assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 4 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

--

## NSN 5305-01-283-9898

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0