## NSN 5305-01-284-1357

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-1357 **Thread Class:** Unf-2a **Thread Direction:** Right-hand Thread Length: Between 0.464 inches and 0.495 inches **Fastener Length:** Between 0.844 inches and 0.875 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches **First Diameter From Head:** Between 0.135 inches and 0.140 inches **Second Diameter From Head:** 0.380 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 80000 pounds per square inch **Externally Relieved Body Diameter Quantity:** Material: Steel comp 304 or steel comp 316 **Material Specification:** Qq-s-763 federal specification all material responses or 66 federal standard all material responses **Surface Treatment: Passivate Surface Treatment Specification:** Astm a380 assn standard single treatment response **Thread Series Designator:** Unf Shelf Life: N/a

--

**Unit Of Measure:** 

## NSN 5305-01-284-1357

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0