

View Online at <https://aerobasegroup.com/nsn/5305-01-284-1364>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.262 inches and 0.369 inches

**Fastener Length:**

Between 0.407 inches and 0.438 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.257 inches and 0.279 inches

**Locking Feature:**

Pellet threads

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.138 inches

**Thready Qty Per Inch (tpi):**

32

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Product Name:**

Navy special project

**Color:**

Black fastener

**Material:**

Steel comp 302 fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l fastener

**Material Specification:**

Qq-s-763 federal specification 1st material response fastener or astm a582 assn standard 2nd material response fastener or astm a582 assn standard 3rd material response fastener or qq-s-763 federal specification 4th material response fastener or qq-s-763 federal specification 5th material response fastener

**Surface Treatment:**

Oxide fastener

**Surface Treatment Specification:**

Mil-c-13924 cl2 military specification single treatment response fastener

**Thread Series Designator:**

Unc

**Specification Or Standard:**

1 type and 2 style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-c-13924 spec.