## NSN 5305-01-284-2488

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-2488 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.710 inches and 0.760 inches **Fastener Length:** Between 1.470 inches and 1.500 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.949 inches and 1.019 inches **Grip Diameter:** Between 0.4990 inches and 0.4995 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.500 inches **Grip Length:** Between 0.740 inches and 0.760 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 20 **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Surface Finish:** 63.0 microinches bearing surface of head **Product Name:** Navy special project Color: Red threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Surface Treatment:** Phosphate **Thread Series Designator:** Unjf

N/a

Shelf Life:

## NSN 5305-01-284-2488

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0