# NSN 5305-01-284-3338

Machine Screw - Page 1 of 1

View Online at https://aerobasegroup.com/nsn/5305-01-284-3338



#### **Thread Class:**

3a

**Thread Direction:** 

**Right-hand** 

### Thread Length:

Between 0.245 inches and 0.276 inches

#### Fastener Length:

Between 0.281 inches and 0.312 inches

#### **Head Style:**

Flat countersunk

#### Head Diameter:

Between 0.126 inches and 0.172 inches

#### Internal Drive Style:

Torque set

#### **Thread Diameter:**

0.086 inches

### Thready Qty Per Inch (tpi):

56

### Min. Tensile Strength (psi):

140000 pounds per square inch

#### Hardness Rating:

Between 248.0 brinell standard and 341.0 brinell standard

#### **Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

#### Screw Material:

Iron alloy 660

#### **Screw Material Specification:**

Asm 5732 assn standard single material response

#### Screw Surface Treatment:

Passivate

#### **Screw Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

#### **Thread Series Designator:**

Unjc

#### Shelf Life:

N/a

## Unit Of Measure:

---

#### Demilitarization:

No

Fiig:

A500d0