

View Online at <https://aerobasegroup.com/nsn/5305-01-284-4747>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.424 inches and 0.464 inches

Fastener Length:

Between 0.872 inches and 0.892 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.264 inches and 0.303 inches

Head Height:

0.012 inches

Grip Diameter:

Between 0.1890 inches and 0.1895 inches

Internal Drive Style:

Hexagon

Thread Diameter:

0.190 inches

Grip Length:

Between 0.428 inches and 0.448 inches

Width Across Flats:

Between 0.1253 inches and 0.1270 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Special Features:

Cut three equal keyways, 120 degrees

Material:

Iron alloy 660

Material Specification:

Ams 5732 assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0