NSN 5305-01-284-5240

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-5240 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.050 inches and 0.070 inches **Fastener Length:** 0.175 inches **Head Style:** Fillister **Head Diameter:** 0.344 inches **Head Height:** 0.045 inches **First Diameter From Head:** 0.170 inches **Second Diameter From Head:** 0.216 inches **Third Diameter From Head:** 0.047 inches **Fourth Diameter From Head:** 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 0.040 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 0.100 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 0.185 inches Distance From Largest Bearing Surface Of Head To End Of Fourth Diameter: 0.175 inches **Internal Drive Style: Thread Diameter:** 0.216 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 4

Material:

Steel comp 303

Material Specification:

Ams5640 assn standard single material response

NSN 5305-01-284-5240

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment:
Passivate
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A003b0