## NSN 5305-01-284-5260

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-5260

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.378 inches and 0.428 inches
Fastener Length:
Between 0.700 inches and 0.730 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.3504 inches and 0.3988 inches
Grip Diameter:
Between 0.2485 inches and 0.2495 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.250 inches
Grip Length:
Between 0.302 inches and 0.322 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5737 assn standard single material response or ams 5731 assn standard single material response or ams 5732 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1581 professional/industrial association standard
Shelf Life:
N/a

## Unit Of Measure:

## NSN 5305-01-284-5260

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

