NSN 5305-01-284-5756

Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-5756

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.325 inches and 0.375 inches
Fastener Length:
Between 0.345 inches and 0.375 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.176 inches and 0.183 inches
Head Height:
Between 0.108 inches and 0.112 inches
Hole Diameter:
0.036 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.112 inches
Width Across Flats:
0.093 inches
Hole Quantity:
2
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Hardness Rating:
80.0 rockwell b
Minimum Yield Strength:
30000 pounds per square inch
Hole Configuration Style:
Round internal hexagon
Product Name:
Navy special project
Material:
Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7
Surface Treatment:

Passivate

NSN 5305-01-284-5756

Socket Head Cap Screw - Page 2 of 2



Surface Treatment Spec	ific	ation:
------------------------	------	--------

Qq-p-35 federal specification single treatment response

Thread Series Designator:

Unrc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0