NSN 5305-01-284-5761

Close Tolerance Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-284-5761



Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.476 inches and 0.526 inches	
Fastener Length:	
Between 1.424 inches and 1.454 inches	
Head Style:	
Pan no. 2	
Head Diameter:	
Between 0.597 inches and 0.612 inches	
Head Height:	
Between 0.176 inches and 0.188 inches	
Grip Diameter:	
Between 0.3115 inches and 0.3120 inches	
Internal Drive Style:	
Torque-set ribbed	
Thread Diameter:	
0.312 inches	
Grip Length:	
Between 0.928 inches and 0.948 inches	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Surface Finish:	
63.0 microinches bearing surface of head	
Material:	
Iron alloy 660	
Material Specification:	
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams573	37 assn standard single
material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Specification Data:	
80205-nas1578 professional/industrial association standard	
Shelf Life:	

Shelf Life:

N/a

NSN 5305-01-284-5761

Close Tolerance Screw - Page 2 of 2

Unit Of Measure:

Demilitarization:

No

Fiig:

A003b0

