## NSN 5305-01-284-5761

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-5761

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.476 inches and 0.526 inches
Fastener Length:
Between 1.424 inches and 1.454 inches
Head Style:
Pan no. 2
Head Diameter:
Between 0.597 inches and 0.612 inches
Head Height:
Between 0.176 inches and 0.188 inches
Grip Diameter:
Between 0.3115 inches and 0.3120 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.312 inches
Grip Length:
Between 0.928 inches and 0.948 inches
Thready Qty Per Inch (tpi):
24
Min. Tensile Strength (psi):
160000 pounds per square inch
Surface Finish:
63.0 microinches bearing surface of head
Material:
Iron alloy 660
Material Specification:
Ams5731 assn standard single material response or ams5732 assn standard single material response or ams5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1578 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-284-5761

Close Tolerance Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0