## NSN 5305-01-284-9673

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-284-9673

view Offilite at https://aerobasegroup.com/hist//3005-01-204-3075
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.483 inches and 0.656 inches
Fastener Length:
Between 0.609 inches and 0.656 inches
Head Style:
Hexagon
Head Height:
Between 0.105 inches and 0.120 inches
Width Between Flats:
Between 0.305 inches and 0.314 inches
Hole Diameter:
Between 0.046 inches and 0.056 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.190 inches
Hole Quantity:
3
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Hardness Rating:
Between 36.0 rockwell c and 40.0 rockwell c
Screw Material:
Steel comp e4340 or steel comp 8740
Screw Material Specification:
Mils-5000 military specification 1st material response or mils-6049 military specification 2nd material response or ams 6322 assn standard
2nd material response
Screw Surface Treatment:
Cadmium and chromate
Head Hole Configuration Style:
Hexagon flats
Thread Series Designator:
Unjf
Specification Data:
80205-nas1801 professional/industrial association standard
Shelf Life:

N/a

## NSN 5305-01-284-9673

Machine Screw - Page 2 of 2



Demilitarization:
No
Fiig:

**Unit Of Measure:** 

Mil-std (military Standard):

spec.

A500d0