Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-0525

| Thread Class: | |
|--|---------|
| 2a | |
| Thread Direction: | |
| Right-hand | |
| Thread Length: | |
| 1.750 inches | |
| Fastener Length: | |
| Between 2.156 inches and 2.250 inches | |
| Head Style: | |
| Flat countersunk | |
| Head Diameter: | |
| Between 0.308 inches and 0.332 inches | |
| Locking Feature: | |
| Pellet threads | |
| Internal Drive Style: | |
| Slot | |
| Thread Diameter: | |
| 0.164 inches | |
| Thready Qty Per Inch (tpi): | |
| 32 | |
| Countersink Angle: | |
| Between 80.0 degrees and 82.0 degrees | |
| Product Name: | |
| Navy special project | |
| Color: | |
| Black fastener | |
| Material: | |
| Steel comp 302 fastener or steel comp 303 fastener or steel comp 303se fastener or steel comp 304 fastener or steel comp 304l faste | er |
| Material Specification: | |
| Qq-s-763 federal specification 1st material response fastener or astm a582 assn standard 2nd material response fastener or astm a58 | 32 assn |
| standard 3rd material response fastener or qq-763 federal specification 4th material response fastener or qq-s-763 federal specification | on 5th |
| material response fastener | |
| Surface Treatment: | |
| Oxide fastener | |
| Surface Treatment Specification: | |
| Mil-c-13924 cl2 military specification single treatment response fastener | |
| Thread Series Designator: | |
| Unc | |
| Specification Or Standard: | |
| 1 type and 2 style | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |

NSN 5305-01-285-0525

Socket Head Cap Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.