## NSN 5305-01-285-2009

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-2009 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.141 inches and 0.172 inches **Fastener Length:** Between 0.408 inches and 0.438 inches **Head Style:** Hexagon **Head Height:** Between 0.080 inches and 0.093 inches Width Between Flats: Between 0.244 inches and 0.250 inches **First Diameter From Head:** Between 0.090 inches and 0.095 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.236 inches and 0.297 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 140000 pounds per square inch **Externally Relieved Body Diameter Quantity: Product Name:** Navy special project Material: Steel comp 4037 **Material Specification:** Ams 6300 assn standard single material response **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 3 federal specification single treatment response **Thread Series Designator:** Unc Shelf Life:

N/a

## NSN 5305-01-285-2009

Externally Relieved Body Screw - Page 2 of 2



			ure:	

--

Demilitarization:

No

Fiig:

A003b0