NSN 5305-01-285-2751

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-2751
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
Between 0.350 inches and 0.370 inches
Fastener Length:
Between 1.850 inches and 1.861 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.357 inches and 0.375 inches
Head Height:
Between 0.177 inches and 0.187 inches
Shoulder Diameter:
0.246 inches first shoulder and 0.248 inches first shoulder
Shoulder Length:
1.500 inches first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
0.190 inches
Width Across Flats:
0.125 inches
Thready Qty Per Inch (tpi):
24
Shoulder Shape:
Round first shoulder
Material:
Steel comp 301 or steel comp 302 or steel comp 302b or steel comp 303 or steel comp 303se or steel comp 304 or steel comp 304l or
steel comp 305 or steel comp 308 or steel comp 309 or steel comp 309s or steel comp 310 or steel comp 310s or steel comp 314 or
steel comp 316 or steel comp 316l or steel comp 317 or steel comp 321 or steel comp 347 or steel comp 348 or steel comp 384 or steel
comp 385
Surface Treatment:
Nickel grip
Surface Treatment Specification:
Qq-n-290 cl 1 gr g federal specification single treatment response grip
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:

NI

Demilitarization:

NSN 5305-01-285-2751

Shoulder Screw - Page 2 of 2



Fiig:

A003b0