

View Online at <https://aerobasegroup.com/nsn/5305-01-285-2753>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.444 inches and 0.494 inches

Fastener Length:

Between 1.704 inches and 1.734 inches

Head Style:

Fillister countersunk

Head Diameter:

Between 0.390 inches and 0.395 inches

Head Height:

0.015 inches

Grip Diameter:

Between 0.2485 inches and 0.2495 inches

Internal Drive Style:

High-torque

Thread Diameter:

0.250 inches

Grip Length:

Between 1.240 inches and 1.260 inches

Features Provided:

Cetyl alcohol lubricant

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

125000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Color:

White top of head

Material:

Steel comp xm-13

Surface Treatment:

Aluminum

Surface Treatment Specification:

Mil-c-83488, type 2 class 3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.