## NSN 5305-01-285-2753

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-285-2753 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.444 inches and 0.494 inches **Fastener Length:** Between 1.704 inches and 1.734 inches **Head Style:** Fillister countersunk **Head Diameter:** Between 0.390 inches and 0.395 inches **Head Height:** 0.015 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** High-torque **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.240 inches and 1.260 inches **Features Provided:** Cetyl alcohol lubricant Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 125000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Color: White top of head Material: Steel comp xm-13 **Surface Treatment:** Aluminum **Surface Treatment Specification:** Mil-c-83488, type 2 class 3 military specification single treatment response **Thread Series Designator:** Unjf

Shelf Life:

N/a

## NSN 5305-01-285-2753

Close Tolerance Screw - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.